



PERFORMANCE FLUIDS

SALES SPECIFICATION

Effective: as from March 01, 2014

Exxsol™ DSP 100/160

Hydrocarbon Fluid

Property	Units	Method	Specification
Appearance	-	EC-A-A01	Bright & Clear
Aromatic content	wt%	UV1	0.500 max
Benzene content	mg/kg	GC2	50 max
Colour, Saybolt	-	ASTM D 6045	+30 min
Density at 15°C	kg/m ³	ISO 12185	737 – 757
Distillation range	°C	ASTM D 86	
Initial Boiling Point			98 min
Dry Point			166 max

Values may be determined by one or more ExxonMobil test methods equivalent to industry standard test methods. Applicable sampling and testing methods are subject to change without notice and are available for review on request.

The values indicated in this document may deviate from the test method requirements by the number of significant figures shown.

©2014 Exxon Mobil Corporation. To the extent the user is entitled to disclose and distribute this document, the user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. You may not copy this document to a Web site. ExxonMobil does not guarantee the typical (or other) values. Analysis may be performed on representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials, or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly steward. ExxonMobil, The ExxonMobil Emblem, the "Interlocking X" Device, Escaid, Exx-Print, Exxsol, Han, Isopar, Nappar, Somentor, Varsoi and Solvesso are trademarks of Exxon Mobil Corporation.